

GY Series

MODEL GYQ84

PEDESTAL MOUNTED BOTTLE FILLER
WITH BI-LEVEL DRINKING FOUNTAIN

STANDARD FEATURES

- Adult ADA compliant
- Pushbutton and hands free sensor operated bottle filler
- Battery pack 6-AA
- Laminar flow water supply to bottle filler
- Resistant to sunlight, heat, moisture and wear
- 18 Gage, 304 stainless steel drinking Fountain bowls
- 12 Gage, heavy duty stainless steel construction with corrosion and scratch resistant finish
- Stainless steel, anti-rotation non-squirt bubbler
- 100 mesh inlet strainer
- Lead and cyst filter (Not available with FRU option)
- Access cover, heavy duty stainless steel, Vandal resistant

SUGGESTED SPECIFICATIONS

Pedestal mounted bottle filler with bi-level drinking fountain shall be Murdock model GYQ84. Construction shall be 12 gage, all stainless steel with 18 gage stainless steel fountain bowls. Pedestal shall have four mounting holes. Access covers shall be secured with vandal-resistant stainless steel screws. Bottle filler shall be activated by a 9 volt sensor or a pushbutton as standard. Unit shall contain a 100 mesh inlet strainer, lead and cyst filter, 6-AA battery pack and laminar flow spout. Self-closing pushbuttons, needing less than 5 pounds force, shall activate internally mounted valves with adjustable stream regulators. Bubblers shall be stainless steel with non-squirt feature and operate on water pressure range of 20-105 psig. Fountain is certified to ANSI A117.1, Public Law 111-380 (NO-LEAD), CHSC 116875 and NSF/ANSI 61, Section 9. Fixture meets ADA and ADA Standing Person, requirements when mounted appropriately.



Model GYQ85-PF Shown

MODEL:

(Must Specify)

- | | |
|--------------------------------|-----------------------------|
| <input type="checkbox"/> GYQ84 | Satin Stainless Finish |
| <input type="checkbox"/> GYQ85 | Green Powder-Coated (Shown) |
| <input type="checkbox"/> GYQ86 | Red Powder-Coated |
| <input type="checkbox"/> GYQ87 | Blue Powder-Coated |

OPTIONAL ACCESSORIES

(additional costs may be incurred)

- | | |
|--------------------------------|--|
| <input type="checkbox"/> -CV | Cartridge valve on fountains
(Not available with freeze-resistant valve) |
| <input type="checkbox"/> -FRU3 | Underground freeze-resistant, 3 valves ¹
(Less filter and sensor) |
| <input type="checkbox"/> -FRU4 | Underground freeze-resistant, 4 valves ¹
(Less filter and sensor) |
| <input type="checkbox"/> -IAP | In-ground anchor plate |
| <input type="checkbox"/> -LOGO | Customer specified logo |
| <input type="checkbox"/> -MO | Bottle filler operated by pushbutton only
(Standard with freeze-resistant valves) |
| <input type="checkbox"/> -PF | Pet fountain ¹ |

Option Notes:

¹See separate option sheet

Complies
with the
following
standards:



Federal
Public Law
111-380
(No Lead)



Member of
U.S. Green
Building
Council



Recyclable
Product





Water
Conserving
Product

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


GY Series

MODEL GYQ84

PEDESTAL MOUNTED BOTTLE FILLER
WITH BI-LEVEL DRINKING FOUNTAIN



**OPTIONAL -PF
PET FOUNTAIN
DETAIL**



* Valve specifications:
Minimum/Maximum Pressure
30 to 100 psi.

Murdock Mfg.™ warrants that its products are free from defects in material or workmanship under normal use and service for a period of one year from date of shipment. Murdock's liability under this warranty shall be discharged solely by replacement or repair of defective material, provided Murdock™ is notified in writing within one year from date of shipment, F.O.B. Industry, California.

SELECTION SUMMARY
& APPROVAL FOR
MANUFACTURING

Model Number & Options _____ Quantity _____

Company _____

Contact _____ Title _____

Signature _____ Date _____
(Approval for Manufacturing)

All dimensions are subject to manufactures tolerance of plus or minus 1/2" nominal and subject to change without notice. Murdock assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. Murdock Mfg.™, Member of Morris Group International™. Please visit www.murdockmfg.com for most current specifications.